### **Quick Selection Guide**



### **Building Integration System / Access Professional Edition Access Easy Controller Access Engine** The Bosch Access Easy Controller (AEC) is your choice for The Bosch Access Professional Edition (APE) is your choice for The Bosch Access Engine (ACE) is your choice for enterprise small and medium sized access control solutions. The flexible APE access control solutions. The Bosch Access Engine is part of the web-based entry level out of the box access control. The web interface is hosted from the Access Easy Controller hardware. client-server architecture grows with your needs and can even be Building Integration System (BIS) from Bosch which allows you to Easy to install, easy to deploy, easy to operate. upscale to the Bosch Access Engine without replacement of access fully integrate access control with your other security, safety and control hardware components save guarding your investment. building management systems.

<b>General Features</b>	AEC	APE	ACE / BIS
Hardware Compatibility	AEC	AMC Wiegand, AMC RS485	AMC Wiegand, AMC RS485
Software Compatibility	Microsoft Windows XP SP3 Microsoft Windows Vista Microsoft Windows 7 (32 and 64 bit) Linux OS *	Microsoft Windows 2000 Microsoft Windows XP Professional Microsoft Server 2003 (32 bit) Microsoft Windows 7 (32 and 64 bit)	Microsoft Server 2003 (32 bit) Microsoft Server 2008 (32 and 64 bit) Microsoft Server 2008 R2 (64 bit) Microsoft Windows XP SP3 Microsoft Windows 7 (32 and 64 bit)
Webserver Connectivity	Yes	No	Yes
Browser Compatibility	Internet Explorer 7/8/9, Mozilla Firefox 5.0*, Google Chrome*	N.A.	Internet Explorer 8/9
Access Control Management	Yes	Yes	Yes
Visitors Management	No	No	Yes, up to 500
Intrusion Integration	Arm/disarm over reader (contact interface)	Arm/disarm over reader (contact interface)	Full integration or Arm/disarm over reader (contact interface)
Video Integration	Yes	Yes	Yes
Offline Locking System	No	No (selected market only)	No
Supported Languages	English, German, Dutch, French, Spanish, Hungarian, Portuguese, Traditional Chinese, Simplified Chinese, Thai	English, German, Dutch, Polish, French, Simplified Chinese, Russian, Spanish, Portuguese (Brazil)	English, German, Dutch, French, Russian, Spanish, Hungarian, Portuguese, Traditional Chinese, Simplified Chinese

<sup>\*</sup> Only access function no video support

# Access Control and Management Systems **Quick Selection Guide**



Access Features	AEC	APE	ACE / BIS
Max. Number of Remote Workstation	Unlimited *	16	Unlimited *
Max. Number of Readers / Cameras	4-32 / 128	128/128	Unlimited **
Supported Reader Interfaces	Wiegand	Wiegand, RS485	Wiegand, RS485
Biometric Support	Fingerpint	Fingerpint	Fingerpint
Max. Number of Relay Outputs Points	64	2048*	Unlimited ***
Max. Number of Entrance	32	128 (Entrance with 1 reader)	Unlimited ****
Remote Door Control	Yes	Yes	Yes
Max. Number of Active Cardholders	20.480	10.000	20.000 to 200.000 on projectbase
Cards per Person	1	Up to 3	1
Access Modes	Card only, PIN only, PIN or Card	Card only, PIN only, PIN and / or Card	Card only, PIN only, Card and PIN
PIN Codes Types	Verification PIN, Door PIN, Arming PIN	Verification PIN, Door PIN, Identification PIN, IDS Arming PIN, (IDS = Intrusion Detection System)	Verification PIN, Door PIN, IDS arming PIN (IDS = Intrusion Detection System)
PIN Codes	4 to 7 digit	4 to 8 digit	4 to 8 digit
Online Swipe	Yes	Yes	No
Mapviewer	No	No	Yes
Event Management	Yes	Yes	Yes
Badge Design	No	Yes	Yes
Alarm List	Yes	Yes	Yes
Time Models	254	255	255
Periods / Time Models	4	3	255
Max. Number of Time Profiles	254	255	255
Max. Number of Access Authorizations	254	255	255
Max. Number of Area / Time Authorizations	254	255	255
Special Days	32	255	255
SMS / Email Notification	Yes	No	No
Elevator	Yes, up to 64 floors	Yes, up to 16 floors	Yes, up to 56 floors
Parking Lot	Yes	No	Yes
	* Concurrent 8	* Max. 128 AMC's per AMC	* BIS does use IIS which is limiting factor

Concurrent 8

Max. 128 AMC's per AMC 1 x 16I/O unit can be connected

BIS does use IIS which is limiting factor

<sup>\*\*</sup> Based on VIE limit

<sup>\*\*\*</sup> Per AMC 3 x 16I/O units can be connected

<sup>\*\*\*\* 800</sup> entrances per MAC in average

## Access Control and Management Systems **Quick Selection Guide**



Video Features	AEC	APE	ACE / BIS
Live View and Playback	Yes	Yes	Yes
Video Alarm Verification	Yes	Yes	Yes
Video Verification	Up to 3 / Entrance	Up to 5 / Entrance	Free programmable using, Misc. & action plans or the Video Engine
Camera Groups	No	No	Yes
Alarm and Logbook Camera	3	1 / Entrance	Free programmable using, Misc. & action plans or the Video Engine